

FUEL TANK CALIBRATION			
GROUND POSITION		MAIN	
AUXILIARY		MAIN	
Gage	Actual	Gage	Actual
10 GALS.	25 GALS.	0 GALS.	0-27 GALS.
25 GALS.	47 GALS.	40 GALS.	54 GALS.
50 GALS.	75 GALS.	100 GALS.	121 GALS.
75 GALS.	91 GALS.	150 GALS.	161 GALS.
F	100 GALS.	200 GALS.	203 GALS.
		225 GALS.	228 GALS.
		250 GALS.	253 GALS.
		260 GALS.	263/272 GALS.

TP06985-03

WARNING

**REMOVE FIREWALL
EXTENSIONS COVER WHEN
OPERATING RADIO ON
GROUND TO PREVENT
MODULATOR OR DYNAMITOR
FROM OVERHEATING**

PARKING BRAKE

●



COCKPIT
LIGHTS MASTER
ON
OFF

LIGHTS		
WINGS NAV LIGHTS	TAIL NAV LIGHTS	LDG LIGHTS
ON	ON	ON
OFF	OFF	OFF

ALIGHTING GEAR OPERATING INSTRUCTIONS


TO RAISE FLAPS - HANDLE UP, LEAVE UP.
TO FULLY LOWER FLAPS - HANDLE DOWN, LEAVE DOWN.
TO PARTIALLY LOWER FLAPS - HANDLE DOWN, RETURN
TO NEUTRAL AT DESIRED FLAP ANGLE.

GAGE
 S
T
A
R
T
E
R
 ERGIZE

Diagram illustrating the 4.C. TYPE battery terminal layout. The terminals are labeled: OFF BAT., L, R, and BOTH. The central circle represents the battery body.

BATTERY

ON



OFF

BATTERY

ON



OFF